

# SK-102

## SlimKey™ Keyboard with HulaPoint™

iKey's SlimKey™ SK-102 keyboard provides full-size versatility in a rugged, compact design, with the added convenience of an integrated HulaPoint™. The SlimKey™ SK-102 is engineered to meet NEMA 4X protection from dust, water and corrosive liquids, the SK-102 is ideal for use in environments ranging from manufacturing to material handling to medical settings. The large numeric pad on the SK-102 allows for easy data entry, while the robust polycarbonate case is durable in the roughest of environments.



### Technical Specifications

Certifications	NEMA 4X UL60950, FCC Part 15 Class B
Shock	3x11 ms pulses of 50g on each of 3 axes
Cable	LENGTH: 10' straight (3 m)
Key Switch	MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.05 oz +/- 1.06 oz (200g +/-30g) FEEDBACK: Tactile with mechanical snap
Vibration	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
Power	PS/2: KEYBOARD: 50mA@5V (from Keyboard port) HULAPOINT: 35mA@5V (from Mouse port) USB: 85mA@5V (from CPU port)
Flammability	PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94HB
Compatibility	PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems USB KEYBOARD/HULAPOINT: All Windows and Macintosh OS
Temperature Range	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)
Weight	1.5 lbs +/- 0.10 lbs (0.68 kg +/- 0.05 kg)
Warranty	1 year limited warranty
Humidity	100%
Dimensions	14.60" x 5.55" x 1.05" (w-h-d) 370.8mm x 141mm x 26.7mm
Model Numbers	

### Features and Benefits

- 12 Function Keys
- MS Windows Function Keys
- USB and PS/2 configurations available
- Integrated HulaPoint Pointing Device
- Slim, Compact Design